

Technical Data Sheet

HOVACO Tile Adhesive C2TE

Product Description :

HOVACO C2TE is a high-performance cement-based tile adhesive designed for the installation of ceramic and porcelain tiles on floors and walls. Suitable for interior and exterior applications where enhanced adhesion and extended open time are required.

Classification:

According to EN 12004
Classification: C2TE

Application Areas:

- Ceramic and porcelain tiles
- Interior and exterior walls
- Floors with moderate traffic
- Cement-based substrates
- Renovation projects

Advantages:

- High adhesion strength
- Reduced slip (T)
- Extended open time (E)
- Suitable for porcelain tiles
- Reliable performance in demanding conditions

Technical Data Table(at +23°C and 50% RH)

Property	Value
Initial adhesion strength	1.15 N/mm ²
Adhesion after 30 min	0.86 N/mm ²
Open time	≥ 30 min
Slip	0.37 mm
Pot life	approx. 3 hours
Water demand	6 - 6.5 L per 25 kg
Coverage	up to 5 m ² per bag
Packaging	25 kg bag
Color	Grey

Mixing:

- Add 6-6.5 L clean water per 25 kg bag
- Mix mechanically for 2-3 minutes until homogeneous
- Let rest 5 minutes and remix before use

Application Instructions:

- Substrate must be clean and sound
- Apply with suitable notched trowel
- Install tiles within open time and protect for 24 hours

Packaging & Storage:

- Available in 25 kg multi-layer paper bags
- Store in a dry and covered area
- Keep away from moisture and direct sunlight
- Shelf life: 12 months in original unopened packaging

Technical data may vary depending on site conditions.